

## MATERIAL DATA SHEET

DESCRIPTION

**BLACK MARINE DIESEL EXHAUST  
HOSE 28MM OD X 19MM ID**



ORDER CODE

**MDE 593**

| PARAMETER   | VALUE  |
|---|--|
| MATERIAL  | BLACK NBR/CR RUBBER COVER OVER NBR INNER WITH SYNTHETIC TEXTILE FABRICS WITH STEEL HELIX REINFORCEMENT |
| INTERNAL DIAMETER   | Ø19MM  |
| EXTERNAL DIAMETER   | Ø28MM  |
| WORKING PRESSURE  | 45PSI  |
| BURST PRESSURE  | 225PSI   |
| MINIMUM BEND RADIUS   | 60MM   |
| TEMPERATURE RANGE   | -30°C TO +100°C  |
| LLOYDS APPROVAL   | 99/00027(E1)APP  |
| DNV APPROVAL  | S-3597APP  |
| RINA APPROVAL   | DIP/4855/03/CS/E/1   |
| <b><u>GENERAL CHARACTERISTICS</u></b>   |  |
| <ul style="list-style-type: none"><li>• VERY FLEXIBLE AND ROBUST MARINE DIESEL EXHAUST HOSE THAT CAN BE USED FOR FUEL</li></ul> |  |

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.