

## MATERIAL DATA SHEET

DESCRIPTION

**WHITE SEAMSEAL BUTYL NON  
SETTING BEDDING MASTIC 380ML**



ORDER CODE

**S 3285**

PARAMETER	VALUE
MATERIAL	WHITE SYNTHETIC RUBBER POLYMER
DENSITY	1.6G/CM <sup>3</sup>
SLUMP (UP TO 20MM X 10MM VERTICAL CHANNEL)	NIL
VOLATILE CONTENT	6 – 8%
MOVEMENT ACCOMMODATION	±5%
SHRINKAGE	8% (APPROX)
SERVICE TEMPERATURE RANGE	-20°C TO +80°C
APPLICATION TEMPERATURE RANGE	+5°C TO 30°C
SERVICE LIFE (PREDICTED)	10+ YEARS
SHELF LIFE	12 MONTHS
WORKING TIME	20MINS (APPROX)
<b><u>GENERAL CHARACTERISTICS</u></b>	
<ul style="list-style-type: none"><li>• NON-DRYING BEDDING SEALANT</li><li>• GOOD MOULD RESISTANCE</li><li>• GOOD ADHESION TO WOOD, BRICK, CONCRETE, GLASS, AND MANY METAL SURFACES</li></ul>	

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.