

MATERIAL DATA SHEET

DESCRIPTION

**RIGID PVC FENDER WITH FLEXIBLE
INSERT – 3.65 METRE LENGTH**



ORDER CODE

PFR 192

PARAMETER	VALUE
MATERIAL - BASE	BLACK PVC
SPECIFIC GRAVITY (ASTM D792 1986 METHOD A)	1.51
HARDNESS	95° SHORE A
TENSILE STRENGTH (BS 2782 METHOD 320C 1976)	39MPA
VICAT SOFTENING POINT	79°C
TEMPERATURE RANGE	-20°C TO +60°C
MATERIAL - INSERT	BLACK PVC
DENSITY (BS2872 620A)	1.24G/CM ³
HARDNESS	67° SHORE A
BSS SOFTNESS NUMBER (BS2872 365)	58
TENSILE STRENGTH (BS2872 320A)	18.4MN/M ²
ELONGATION @ BREAK (BS2872 320A)	390%
100% MODULUS (BS2872 320A)	7.58MN/M ²
COLD FLEX TEMPERATURE (BS2872 150B)	-26°C

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.