


MATERIAL DATA SHEET

DESCRIPTION

**BLACK SOLID NEOPRENE STRIP
25MM X 5MM X 5M ROLL**



ORDER CODE

SN 34

PARAMETER	VALUE
MATERIAL	BLACK NEOPRENE
DIMENSIONAL TOLERANCE – WIDTH – THICKNESS	±0.5MM ±0.55MM
DENSITY	1.4G/CM ³
HARDNESS	65 – 75° SHORE A
TEMPERATURE RANGE	-20°C TO +80°C
TENSILE STRENGTH (DIN 53577)	5MPA (MIN)
COMPRESSION SET	35%
ELONGATION @ BREAK	250%
TEAR RESISTANCE	16KN/M

GENERAL CHARACTERISTICS

RESISTANT TO SOME INORGANIC SALTS, ACIDS AND OZONE. FLAME RETARDANT. MODERATE RESISTANCE TO PETROLEUM BASED PRODUCTS OTHER THAN AROMATIC AND HALOGENATED HYDROCARBONS

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.