

MATERIAL DATA SHEET

DESCRIPTION

**BLACK SPONGE RUBBER HOLLOW D SECTION
(12MM X 12MM NOM) SELF ADHESIVE**



ORDER CODE

SRS 2873

PARAMETER	VALUE
SPONGE MATERIAL	BLACK EXPANDED EPDM
DENSITY RANGE	0.5 – 0.9G/CM ³
WATER ABSORPTION	5% (MAX)
COMPRESSION SET (22 HOURS @ R/T)	50%
OZONE RESISTANCE	EXCELLENT
WEATHER RESISTANCE	EXCELLENT
UV LIGHT RESISTANCE	EXCELLENT
MOULD GROWTH RESISTANCE	VERY GOOD
OIL RESISTANCE	NO
LOW TEMPERATURE FLEXIBILITY (-40°C)	PASS
OVEN AGEING (7 DAYS @ 70°C)	±30%
ADHESIVE TAPE	3M ACRYLIC FOAM
TAPE THICKNESS WITHOUT LINER	0.8MM ± 0.1MM
COLOUR	GREY
DENSITY	650 ± 100KG/M ³

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.

SRS 2873 CONTINUED

ADHESIVE TO EPDM

ADHESIVE LINER SIDE

T-PEEL TO RUBBER (24 HOURS @ R/T)

SHELF LIFE (STORED @ 20°C 50% HUMIDITY)

E2 HEAT ACTIVATED

AR7 ACRYLATE

18N/CM

12 MONTHS