

MATERIAL DATA SHEET

DESCRIPTION

**WHITE TIMBER FOAM P SEAL
50M COIL**



ORDER CODE

TFS 3246

PARAMETER	VALUE
MATERIAL	POLYPROPYLENE BASE INSERT WITH POLYURETHANE FOAM INNER CORE COVERED WITH POLYETHYLENE OUTER SKIN
WORKING DISTANCE RANGE (BS EN12365)	>2MM ≤4MM
LINEAR COMPRESSION FORCE (BS EN12365-2)	>100N/M ≤200N/M
WORKING TEMPERATURE RANGE (BS EN12365)	-40°C TO +70°C
DEFLECTION RECOVERY (BS EN12365-3)	>90%
RECOVERY AFTER AGEING (BS EN12365-4)	>30% TO 40%
GENERAL CHARACTERISTICS	
<ul style="list-style-type: none">• EXCELLENT INSULATION PROPERTIES• GOOD ACOUSTIC PROPERTIES• UV STABLE• NON TOXIC• MOULD AND MILDEW RESISTANT• LOW FRICTION AND HIGH RESISTANCE TO ABRASION, OZONE AND BIOLOGICAL ATTACK• RESISTANT TO MOST PAINTS AND VARNISHES• 10 YEAR LIFE CYCLE	

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.